



Recessed LED spotlight with diffuse light projection

Materials:

thermoplastic polymers, PMMA

Finishes:

chrome plated, aluminium, satin nickel, steel, black touch, white matt

Light source:

SMD LED module

Wiring:

2000mm


Application type:

universal

Installation:

recessed

Patented



Colour appearancenatural whiteColour temperature4300 KLuminous flux390 lmLuminous efficiency130 lm/WCRIRa ≥ 80

Colour appearance warm white 3000 K
Luminous flux 360 Im
Luminous efficiency 120 Im/W

CRI Ra ≥ 80

Colour appearance super warm white **Colour temperature** 2700 K

Colour temperature2700 KLuminous flux360 lmLuminous efficiency120 lm/WCRI $Ra \ge 80$









Code	Watt & Volt	Light colour
12310B	3W @ 12Vdc	warm white

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.





Code	Finish
09	chrome plated
10	aluminium
17	satin nickel
19	steel
46	black touch
54	white matt

	-	Ø57	N
12		ĵ	
1,2		Ø64	

N This drawing shows the spotlight's overall dimensions. See installation manual for more details.

SMALLY XS is a spotlight designed for **recessed installation in a hole Ø57mm** and **just 12mm deep**. It is installed on wood panels with both through and blind holes.

SMALLY XS incorporates a high-performance SMD LED module with no-dot effect technology, ensuring a uniform projection beam without the dot effect.

SMALLY XS PLUS features the innovative **Plug&Play system (patented)**, for easy disconnection of the power cord from the spotlight.



FINISHES



ALUMINIUM (code 10)



BLACK TOUCH (code 46)